

## Optical Supervisory Channel

### Field of the invention

The present invention relates broadly to an optical network, to a method of managing an optical network, and to a network element for use in an optical network.

### Background of the invention

There is a continuing demand for providing more and more user facilities in telecommunications equipment such as an optical network. Those facilities primarily relate to the management of the components within the optical network and the distribution and display of information such as alarm reports, audit logs, alarm logs, status reports and control messages.

The management network controls a channel wavelength called the optical supervisory channel (OSC) which may be transmitted over the network via the Internet protocol (IP). This OSC is usually an out-of-band wavelength, i.e. a wavelength outside the telecommunication wavelength band, which will get transmitted through all of the network elements.

Utilising standard IP routing, the OSC is transmitted unidirectionally in a network. Usually, a standard primary path is chosen for the OSC to follow from a source network element to a destination network element on the network. If a failure occurs in the network along the primary path, then the path of the OSC is interrupted, and as a result an IP time out will eventually occur, notifying the source network element of the interruption. To deal with such failure, the IP datagrams, i.e. the OSC, are re-routed along a secondary path from the source network element to the destination network element. However, this is a time consuming procedure due to the relatively long IP time outs, leaving the management of the network interrupted for an undesirably long period of time.

At least preferred embodiments of the present invention seek to provide an alternative network management system.

### Summary of the invention

In accordance with a first aspect of the present invention there is provided an optical network comprising a network management station, at least one source network element associated with the network management station, and at least one destination network element, wherein the source network element comprises a source proxy for sending an OSC signal in the

form of IP datagrams to the destination network element under the control of the management station, the source proxy being arranged in a manner such that, in use, it sends duplicate IP datagrams along two different optical paths to the destination network element, and wherein the destination network element comprises a destination proxy arranged to pass one of the duplicate IP datagrams into the destination network element for processing and to filter out for disposal the other one.

Accordingly, if a failure occurs along one of the paths one of the duplicated OSC signals will still be received at the source network element for processing, without any downtime caused by IP timeouts.

The source proxy may be arranged in a manner such that, in use, the duplication of the IP datagrams is effected at an IP layer or at an Ethernet layer.

The management function may comprise the distribution of one or more of the group of alarm reports, audit logs, alarm logs, status reports and control messages.

In one embodiment, the optical network is arranged in a manner such that, in use, the management function is being effected via e-mail messages transmitted using the standard IP protocols.

Alternatively or additionally, the optical network may be arranged in a manner such that, in use, the management function is being effected via an HTTP server incorporated in the network element and accessible via a conventional web browser.

The network element may comprise a network node or an in-line amplifier.

Where the optical network is a ring network, the different paths of the duplicated OSC signal preferably comprise transmission paths along opposite directions of the ring network.

Where the optical network is a mesh network, the source proxy may be arranged in a manner such that, in use, it sends at least two identical IP datagrams along at least two different optical paths to the destination network element, and the destination network element comprises a destination proxy arranged to pass one of the IP datagrams into the network element for processing and to filter out for disposal the others.

Where the optical network comprises more than one destination network element, the destination network elements are preferably arranged in a manner such that the OSC is terminated and re-transmitted at each intermediate destination network element.

In a preferred embodiment, the source proxy may be arranged to be capable of also functioning as a destination proxy, and/or the destination proxy may be arranged to be capable of functioning as a source proxy.

In accordance with a second aspect of the present invention there is provided a method of managing an optical network comprising the steps of sending duplicate OSC signals in the form of IP datagrams along two different optical paths to a destination network element, and, at the destination network element, passing one of the duplicate IP datagrams into the destination network element for processing and filtering out for disposal the other one.

In accordance with a third aspect of the present invention there is provided a network element for use in an optical network, the optical network element comprising a source proxy for sending an OSC signal in the form of IP datagrams to a destination network element on the network under the control of a management station, the source proxy being arranged in a manner such that, in use, it sends duplicate IP datagrams along two different optical paths to the destination network element.

The network element may comprise a network node or an in-line amplifier.

The management station may be incorporated in the network element.

The network element may further comprise a destination proxy arranged, in use, to receive duplicate OSC signals from another network element in the form of IP datagrams, the destination proxy being arranged to pass one of the duplicate IP datagrams into the network element for processing and to filter out for disposal the other one.

In accordance with a fourth aspect of the present invention there is provided a network element for use in an optical network, the optical network element comprising a destination proxy arranged to receive duplicate OSC signals in the form of IP datagrams, the destination proxy being arranged to pass one of the duplicate IP datagrams into the network element for processing and to filter out for disposal the other one.

The network element may comprise a network node or an in-line amplifier.

## Brief description of the drawings

Preferred forms of the present invention will now be described, by way of example only, with reference to the accompanying drawings.

Figure 1 is a schematic diagram illustrating an optical network embodying the present invention.

Figure 2 is a schematic diagram illustrating another optical network embodying the present invention.

Figure 3 is an example screen shot illustrative of a management display screen embodying the present invention.

Figure 4 is a schematic diagram illustrating the functional modules of a metro hub embodying the present invention.

Figure 5 is a schematic diagram illustrating the connectivity of a management network embodying the present invention.

## Detailed description of the embodiments

The preferred embodiment described provides an optical network in which OSC signals in the form of IP datagrams are duplicated and then transmitted along the ring network in opposing direction simultaneously, thus providing a 1 + 1 protection mechanism for the OSC.

In figure 1, an optical network in the form of a ring network 10 comprises a plurality of network elements, including a network node 12 which interfaces to subscribers of the ring network 10, and an in-line amplifier unit 14.

The network node 12 and amplifier unit 14 each incorporate HTTP server application units 16, 18 respectively, which are accessible through a desktop PC-type interface 20 incorporated within the network node 12.

Accordingly, a user can monitor and control at least some of the functions and components incorporated in the node 12 and amplifier unit 14 utilising standard TCP/IP communication protocols. This avoids the need for implementing specialised tools within the ring network 10 for those monitoring and controlling functionalities.

The network node 12 and amplifier unit 14 further comprise email application units 26, 28 respectively. The email application units 26, 28 are arranged in a manner such that status

reports on components incorporated in the network node 12 and amplifier unit 14 respectively are being emailed to the user (i.e. to PC-type interface 20), thereby e.g. alerting the user to failures in certain of those components. Again, the email messages are being communicated using standard TCP/IP protocols.

The network node 12 further comprises a proxy 13 through which all management traffic is interfaced onto an OSC on the ring network 10. The proxy 13 is arranged in a manner such that IP datagrams, i.e. a management signal destined for e.g. the amplifier unit 14, are duplicated and sent simultaneously around the ring network 10 in opposite directions as indicated by arrows 15 and 17 respectively.

The OSC is terminated and re-transmitted at each intermediate network element, rather than being amplified through in-line amplifiers. For example, the clock-wise transmitted duplicated OSC signal indicated by arrow 17 will be terminated and re-transmitted at amplifier unit 19 and network node 21 before being received at the amplifier unit 14.

The amplifier unit 14 comprises a proxy 23 arranged in a manner such that one of the duplicated OSC signal's is passed into the amplifier unit 14 for further processing, whereas the other one is filtered out for disposal. In the example shown in Figure 1, the management signal indicated by arrow 15 will under normal conditions be received at amplifier 14 prior to the other duplicated management signal 17, which would result in management signal 15 being passed into the amplifier unit 14 by the proxy 23 for further processing, whereas management signal 17 will be filtered out for disposal. However, it will be appreciated by a person skilled in the art that rather than determining which signal to pass or filter out only on a "first received" basis, the determination could also and/or additionally be based on a more complex analysis e.g. a "quality of signal"-type determination, which could favour one over the other due to losses or distortions experienced along the respective path.

Importantly, should a complete failure such as a fibre breakage occur along either of the paths, the other one will then always be passed into the amplifier unit 14 by the proxy 23 for further processing. Accordingly, the optical network configuration shown in Figure 1 avoids downtime in the management of the ring network 10 where a failure along one of the paths occurs, which would otherwise result in significant downtimes as a result of standard IP timeouts.

In the exemplary embodiment shown in Figure 1, the proxies 13 and 25 of the network nodes 12 and 21 respectively, are configured in a manner such that they can act as both source and destination proxies. In other words, management of the ring network 10 may be conducted from either network node 12 or 21, with the proxy of the other network node then performing a functionality similar to the functionality of proxy 23 of the amplifier unit 14.

In another embodiment of the present invention shown in Figure 2 a ring network 100 comprises a plurality of network elements, including network nodes, e.g. 102 which interface to subscribers of the ring network 100, and in-line amplifier units e.g. 104.

Each of the network nodes e.g. 102 and amplifier units e.g. 104 incorporates HTTP server application units, e.g. 106, 108.

Management of the ring network 100 is implemented by utilising a management channel connecting all of the HTTP server application units e.g. 106, 108, using TCP/IP protocols for communication.

Each of the HTTP server application units e.g. 106, 108 have typical communication characteristics such as routing capability to pass-through communications directed to other HTTP server application units and to process communications intended for itself. Each HTTP server application unit is identifiable through a unique address within the TCP/IP protocol communication network.

Each of the network nodes 102, 103 incorporates a proxy 105, 107 respectively, of similar functionality to the proxies 13, 25 (Figure 1) described above. Each of the amplifier units 104, 109 incorporates a proxy 111, 113 respectively of similar functionality as the proxy 23 (Figure 1) described above.

In the embodiment shown in Figure 2 a remote management station 110 is provided for centralised management of the ring network 100. Since the management channel of the ring network 100 utilises TCP/IP protocols for communication, the management station 110 can be remotely connected to any one of the network elements of the ring network 100 through the Internet 112. In such an embodiment, suitable firewall protection 114 should be provided at the HTTP server application unit 106 incorporated within the network node 102 to which the management station 110 is connected in the embodiment shown in Figure 2. This ensures that the network is completely isolated from the publicly accessible Internet 112.

Figure 3 shows an example screen shot 200 illustrative of a management display screen presented to a user at the remote management station 110.

In the described embodiments, the optical ring network comprises a Management Network which overlays the physical and logical topology of the data communication network. The management network enables all Managed Network Elements within the network to be monitored and/or controlled from a Management Terminal.

The Managed Network Elements may comprise e.g. a metro hub, a core hub or a line amplifier. Figure 4 shows a block diagram illustrating the various functional modules at e.g. a metro hub 160.

The metro hub comprises the following functional modules:

- a hub bypass switch connecting the metro hub 400 to the optical network (not shown);
- a management MUX/DEMUX unit 402 for extracting the OSC from the network traffic;
- a coarse wavelength division multiplexing (CWDM) unit 406 for coarse multiplexing/demultiplexing of optical data signals;
- a dense wavelength division multiplexing (DWDM) MUX/DEMUX unit 410 for dense multiplexing/demultiplexing of the data signals;
- a system of trunk interface cards 412, channel switch 414 and line interface cards 416 interfacing to customers (subscribers) 418 of the optical network;
- a management channel Tx/Rx unit 404 interfacing to a management processing unit 403; and
- a proxy 405 of the type of proxies 13, 23 (Figure 1) and 105, 107 (Figure 2) described above incorporated within the management processing unit 403.

The logical connectivity of the Management Network 2100 is shown in Figure 5. The Management Network 2100 comprises two logical channels (importantly not necessarily on two physical optical connections) counter-propagating within the network. The use of two counter-propagating channels ensures that communication of management information between any pair of network elements is not interrupted in the case of any single failure such as e.g. a fibre break. Each counter-propagating channel consists of a set of point-to-point links, e.g. 2102, 2104,

connecting adjacent Managed Network Elements, e.g. 2106. Thus each Managed Network Element 2106 comprises two management receivers 2110*a*, 2110*b* and two management transmitters 2112*a*, 2112*b*. Some terminal equipment, e.g. a Core Hub 2108, may contain multiple Managed Network Elements, in which case the connectivity between these elements is effected internally, and the terminal equipment still has only two sets of management transmitters and receivers.

Within each Managed Network Element, the management signals are multiplexed and demultiplexed with the data signals on each fibre by the Management MUX/DEMUX Units 402 (see Figure 4).

Advantageously, since the management channel connections e.g. 2102, 2104, are established between adjacent Managed Network Elements, they are fully regenerated at each Managed Network Element, and do not require optical amplification.

The management channel connections may comprise signals transmitted outside the gain bandwidth of conventional optical amplifiers, e.g. at a wavelength of around 1510 nm.

Advantageously, the two counter-propagating management signals 2102, 2104 in each link may be transmitted bi-directionally in the same fibre.

In order to avoid problems with backscattered or reflected light from one management signal, e.g. 2102, interfering with the counter-propagating management signal, e.g. 2104, the two management channels may be transmitted on different wavelengths, e.g. 1505 nm and 1515 nm.

The management channel may comprise relatively low bit-rate signals, e.g. around 100 Mb/s, so that dispersion and power budget for the management signals do not restrict the maximum distance between Managed Network Elements.

The transmission format of the management signals may comprise local-area network standards, e.g. full-duplex 100 Mb/s Fast Ethernet, so that the management channel connections may be implemented using low-cost commodity hardware.

Advantageously, the Management multiplexer/de-multiplexer (MUX/DEMUX) Units 402 (see Figure 4) should present minimal insertion loss to non-management channels, in order to maximise the power budget available for data signal transmission.



It will be appreciated by a person skilled in the art that numerous variations and/or modifications may be made to the present invention as shown in the specific embodiments without departing from the spirit or scope of the invention as broadly described. The present embodiments are, therefore, to be considered in all respects to be illustrative and not restrictive.

In the claims that follow and in the summary of the invention, except where the context requires otherwise due to express language or necessary implication, the word “comprising” is used in the sense of “including”, i.e. the feature specified may be associated with further features in various embodiments of the invention.

FIG. 1  
FIG. 2  
FIG. 3  
FIG. 4  
FIG. 5  
FIG. 6  
FIG. 7  
FIG. 8  
FIG. 9  
FIG. 10  
FIG. 11  
FIG. 12  
FIG. 13  
FIG. 14  
FIG. 15  
FIG. 16  
FIG. 17  
FIG. 18  
FIG. 19  
FIG. 20  
FIG. 21  
FIG. 22  
FIG. 23  
FIG. 24  
FIG. 25  
FIG. 26  
FIG. 27  
FIG. 28  
FIG. 29  
FIG. 30  
FIG. 31  
FIG. 32  
FIG. 33  
FIG. 34  
FIG. 35  
FIG. 36  
FIG. 37  
FIG. 38  
FIG. 39  
FIG. 40  
FIG. 41  
FIG. 42  
FIG. 43  
FIG. 44  
FIG. 45  
FIG. 46  
FIG. 47  
FIG. 48  
FIG. 49  
FIG. 50  
FIG. 51  
FIG. 52  
FIG. 53  
FIG. 54  
FIG. 55  
FIG. 56  
FIG. 57  
FIG. 58  
FIG. 59  
FIG. 60  
FIG. 61  
FIG. 62  
FIG. 63  
FIG. 64  
FIG. 65  
FIG. 66  
FIG. 67  
FIG. 68  
FIG. 69  
FIG. 70  
FIG. 71  
FIG. 72  
FIG. 73  
FIG. 74  
FIG. 75  
FIG. 76  
FIG. 77  
FIG. 78  
FIG. 79  
FIG. 80  
FIG. 81  
FIG. 82  
FIG. 83  
FIG. 84  
FIG. 85  
FIG. 86  
FIG. 87  
FIG. 88  
FIG. 89  
FIG. 90  
FIG. 91  
FIG. 92  
FIG. 93  
FIG. 94  
FIG. 95  
FIG. 96  
FIG. 97  
FIG. 98  
FIG. 99  
FIG. 100  
FIG. 101  
FIG. 102  
FIG. 103  
FIG. 104  
FIG. 105  
FIG. 106  
FIG. 107  
FIG. 108  
FIG. 109  
FIG. 110  
FIG. 111  
FIG. 112  
FIG. 113  
FIG. 114  
FIG. 115  
FIG. 116  
FIG. 117  
FIG. 118  
FIG. 119  
FIG. 120  
FIG. 121  
FIG. 122  
FIG. 123  
FIG. 124  
FIG. 125  
FIG. 126  
FIG. 127  
FIG. 128  
FIG. 129  
FIG. 130  
FIG. 131  
FIG. 132  
FIG. 133  
FIG. 134  
FIG. 135  
FIG. 136  
FIG. 137  
FIG. 138  
FIG. 139  
FIG. 140  
FIG. 141  
FIG. 142  
FIG. 143  
FIG. 144  
FIG. 145  
FIG. 146  
FIG. 147  
FIG. 148  
FIG. 149  
FIG. 150  
FIG. 151  
FIG. 152  
FIG. 153  
FIG. 154  
FIG. 155  
FIG. 156  
FIG. 157  
FIG. 158  
FIG. 159  
FIG. 160  
FIG. 161  
FIG. 162  
FIG. 163  
FIG. 164  
FIG. 165  
FIG. 166  
FIG. 167  
FIG. 168  
FIG. 169  
FIG. 170  
FIG. 171  
FIG. 172  
FIG. 173  
FIG. 174  
FIG. 175  
FIG. 176  
FIG. 177  
FIG. 178  
FIG. 179  
FIG. 180  
FIG. 181  
FIG. 182  
FIG. 183  
FIG. 184  
FIG. 185  
FIG. 186  
FIG. 187  
FIG. 188  
FIG. 189  
FIG. 190  
FIG. 191  
FIG. 192  
FIG. 193  
FIG. 194  
FIG. 195  
FIG. 196  
FIG. 197  
FIG. 198  
FIG. 199  
FIG. 200  
FIG. 201  
FIG. 202  
FIG. 203  
FIG. 204  
FIG. 205  
FIG. 206  
FIG. 207  
FIG. 208  
FIG. 209  
FIG. 210  
FIG. 211  
FIG. 212  
FIG. 213  
FIG. 214  
FIG. 215  
FIG. 216  
FIG. 217  
FIG. 218  
FIG. 219  
FIG. 220  
FIG. 221  
FIG. 222  
FIG. 223  
FIG. 224  
FIG. 225  
FIG. 226  
FIG. 227  
FIG. 228  
FIG. 229  
FIG. 230  
FIG. 231  
FIG. 232  
FIG. 233  
FIG. 234  
FIG. 235  
FIG. 236  
FIG. 237  
FIG. 238  
FIG. 239  
FIG. 240  
FIG. 241  
FIG. 242  
FIG. 243  
FIG. 244  
FIG. 245  
FIG. 246  
FIG. 247  
FIG. 248  
FIG. 249  
FIG. 250  
FIG. 251  
FIG. 252  
FIG. 253  
FIG. 254  
FIG. 255  
FIG. 256  
FIG. 257  
FIG. 258  
FIG. 259  
FIG. 260  
FIG. 261  
FIG. 262  
FIG. 263  
FIG. 264  
FIG. 265  
FIG. 266  
FIG. 267  
FIG. 268  
FIG. 269  
FIG. 270  
FIG. 271  
FIG. 272  
FIG. 273  
FIG. 274  
FIG. 275  
FIG. 276  
FIG. 277  
FIG. 278  
FIG. 279  
FIG. 280  
FIG. 281  
FIG. 282  
FIG. 283  
FIG. 284  
FIG. 285  
FIG. 286  
FIG. 287  
FIG. 288  
FIG. 289  
FIG. 290  
FIG. 291  
FIG. 292  
FIG. 293  
FIG. 294  
FIG. 295  
FIG. 296  
FIG. 297  
FIG. 298  
FIG. 299  
FIG. 300  
FIG. 301  
FIG. 302  
FIG. 303  
FIG. 304  
FIG. 305  
FIG. 306  
FIG. 307  
FIG. 308  
FIG. 309  
FIG. 310  
FIG. 311  
FIG. 312  
FIG. 313  
FIG. 314  
FIG. 315  
FIG. 316  
FIG. 317  
FIG. 318  
FIG. 319  
FIG. 320  
FIG. 321  
FIG. 322  
FIG. 323  
FIG. 324  
FIG. 325  
FIG. 326  
FIG. 327  
FIG. 328  
FIG. 329  
FIG. 330  
FIG. 331  
FIG. 332  
FIG. 333  
FIG. 334  
FIG. 335  
FIG. 336  
FIG. 337  
FIG. 338  
FIG. 339  
FIG. 340  
FIG. 341  
FIG. 342  
FIG. 343  
FIG. 344  
FIG. 345  
FIG. 346  
FIG. 347  
FIG. 348  
FIG. 349  
FIG. 350  
FIG. 351  
FIG. 352  
FIG. 353  
FIG. 354  
FIG. 355  
FIG. 356  
FIG. 357  
FIG. 358  
FIG. 359  
FIG. 360  
FIG. 361  
FIG. 362  
FIG. 363  
FIG. 364  
FIG. 365  
FIG. 366  
FIG. 367  
FIG. 368  
FIG. 369  
FIG. 370  
FIG. 371  
FIG. 372  
FIG. 373  
FIG. 374  
FIG. 375  
FIG. 376  
FIG. 377  
FIG. 378  
FIG. 379  
FIG. 380  
FIG. 381  
FIG. 382  
FIG. 383  
FIG. 384  
FIG. 385  
FIG. 386  
FIG. 387  
FIG. 388  
FIG. 389  
FIG. 390  
FIG. 391  
FIG. 392  
FIG. 393  
FIG. 394  
FIG. 395  
FIG. 396  
FIG. 397  
FIG. 398  
FIG. 399  
FIG. 400  
FIG. 401  
FIG. 402  
FIG. 403  
FIG. 404  
FIG. 405  
FIG. 406  
FIG. 407  
FIG. 408  
FIG. 409  
FIG. 410  
FIG. 411  
FIG. 412  
FIG. 413  
FIG. 414  
FIG. 415  
FIG. 416  
FIG. 417  
FIG. 418  
FIG. 419  
FIG. 420  
FIG. 421  
FIG. 422  
FIG. 423  
FIG. 424  
FIG. 425  
FIG. 426  
FIG. 427  
FIG. 428  
FIG. 429  
FIG. 430  
FIG. 431  
FIG. 432  
FIG. 433  
FIG. 434  
FIG. 435  
FIG. 436  
FIG. 437  
FIG. 438  
FIG. 439  
FIG. 440  
FIG. 441  
FIG. 442  
FIG. 443  
FIG. 444  
FIG. 445  
FIG. 446  
FIG. 447  
FIG. 448  
FIG. 449  
FIG. 450  
FIG. 451  
FIG. 452  
FIG. 453  
FIG. 454  
FIG. 455  
FIG. 456  
FIG. 457  
FIG. 458  
FIG. 459  
FIG. 460  
FIG. 461  
FIG. 462  
FIG. 463  
FIG. 464  
FIG. 465  
FIG. 466  
FIG. 467  
FIG. 468  
FIG. 469  
FIG. 470  
FIG. 471  
FIG. 472  
FIG. 473  
FIG. 474  
FIG. 475  
FIG. 476  
FIG. 477  
FIG. 478  
FIG. 479  
FIG. 480  
FIG. 481  
FIG. 482  
FIG. 483  
FIG. 484  
FIG. 485  
FIG. 486  
FIG. 487  
FIG. 488  
FIG. 489  
FIG. 490  
FIG. 491  
FIG. 492  
FIG. 493  
FIG. 494  
FIG. 495  
FIG. 496  
FIG. 497  
FIG. 498  
FIG. 499  
FIG. 500  
FIG. 501  
FIG. 502  
FIG. 503  
FIG. 504  
FIG. 505  
FIG. 506  
FIG. 507  
FIG. 508  
FIG. 509  
FIG. 510  
FIG. 511  
FIG. 512  
FIG. 513  
FIG. 514  
FIG. 515  
FIG. 516  
FIG. 517  
FIG. 518  
FIG. 519  
FIG. 520  
FIG. 521  
FIG. 522  
FIG. 523  
FIG. 524  
FIG. 525  
FIG. 526  
FIG. 527  
FIG. 528  
FIG. 529  
FIG. 530  
FIG. 531  
FIG. 532  
FIG. 533  
FIG. 534  
FIG. 535  
FIG. 536  
FIG. 537  
FIG. 538  
FIG. 539  
FIG. 540  
FIG. 541  
FIG. 542  
FIG. 543  
FIG. 544  
FIG. 545  
FIG. 546  
FIG. 547  
FIG. 548  
FIG. 549  
FIG. 550  
FIG. 551  
FIG. 552  
FIG. 553  
FIG. 554  
FIG. 555  
FIG. 556  
FIG. 557  
FIG. 558  
FIG. 559  
FIG. 560  
FIG. 561  
FIG. 562  
FIG. 563  
FIG. 564  
FIG. 565  
FIG. 566  
FIG. 567  
FIG. 568  
FIG. 569  
FIG. 570  
FIG. 571  
FIG. 572  
FIG. 573  
FIG. 574  
FIG. 575  
FIG. 576  
FIG. 577  
FIG. 578  
FIG. 579  
FIG. 580  
FIG. 581  
FIG. 582  
FIG. 583  
FIG. 584  
FIG. 585  
FIG. 586  
FIG. 587  
FIG. 588  
FIG. 589  
FIG. 590  
FIG. 591  
FIG. 592  
FIG. 593  
FIG. 594  
FIG. 595  
FIG. 596  
FIG. 597  
FIG. 598  
FIG. 599  
FIG. 600  
FIG. 601  
FIG. 602  
FIG. 603  
FIG. 604  
FIG. 605  
FIG. 606  
FIG. 607  
FIG. 608  
FIG. 609  
FIG. 610  
FIG. 611  
FIG. 612  
FIG. 613  
FIG. 614  
FIG. 615  
FIG. 616  
FIG. 617  
FIG. 618  
FIG. 619  
FIG. 620  
FIG. 621  
FIG. 622  
FIG. 623  
FIG. 624  
FIG. 625  
FIG. 626  
FIG. 627  
FIG. 628  
FIG. 629  
FIG. 630  
FIG. 631  
FIG. 632  
FIG. 633  
FIG. 634  
FIG. 635  
FIG. 636  
FIG. 637  
FIG. 638  
FIG. 639  
FIG. 640  
FIG. 641  
FIG. 642  
FIG. 643  
FIG. 644  
FIG. 645  
FIG. 646  
FIG. 647  
FIG. 648  
FIG. 649  
FIG. 650  
FIG. 651  
FIG. 652  
FIG. 653  
FIG. 654  
FIG. 655  
FIG. 656  
FIG. 657  
FIG. 658  
FIG. 659  
FIG. 660  
FIG. 661  
FIG. 662  
FIG. 663  
FIG. 664  
FIG. 665  
FIG. 666  
FIG. 667  
FIG. 668  
FIG. 669  
FIG. 670  
FIG. 671  
FIG. 672  
FIG. 673  
FIG. 674  
FIG. 675  
FIG. 676  
FIG. 677  
FIG. 678  
FIG. 679  
FIG. 680  
FIG. 681  
FIG. 682  
FIG. 683  
FIG. 684  
FIG. 685  
FIG. 686  
FIG. 687  
FIG. 688  
FIG. 689  
FIG. 690  
FIG. 691  
FIG. 692  
FIG. 693  
FIG. 694  
FIG. 695  
FIG. 696  
FIG. 697  
FIG. 698  
FIG. 699  
FIG. 700  
FIG. 701  
FIG. 702  
FIG. 703  
FIG. 704  
FIG. 705  
FIG. 706  
FIG. 707  
FIG. 708  
FIG. 709  
FIG. 710  
FIG. 711  
FIG. 712  
FIG. 713  
FIG. 714  
FIG. 715  
FIG. 716  
FIG. 717  
FIG. 718  
FIG. 719  
FIG. 720  
FIG. 721  
FIG. 722  
FIG. 723  
FIG. 724  
FIG. 725  
FIG. 726  
FIG. 727  
FIG. 728  
FIG. 729  
FIG. 730  
FIG. 731  
FIG. 732  
FIG. 733  
FIG. 734  
FIG. 735  
FIG. 736  
FIG. 737  
FIG. 738  
FIG. 739  
FIG. 740  
FIG. 741  
FIG. 742  
FIG. 743  
FIG. 744  
FIG. 745  
FIG. 746  
FIG. 747  
FIG. 748  
FIG. 749  
FIG. 750  
FIG. 751  
FIG. 752  
FIG. 753  
FIG. 754  
FIG. 755  
FIG. 756  
FIG. 757  
FIG. 758  
FIG. 759  
FIG. 760  
FIG. 761  
FIG. 762  
FIG. 763  
FIG. 764  
FIG. 765  
FIG. 766  
FIG. 767  
FIG. 768  
FIG. 769  
FIG. 770  
FIG. 771  
FIG. 772  
FIG. 773  
FIG. 774  
FIG. 775  
FIG. 776  
FIG. 777  
FIG. 778  
FIG. 779  
FIG. 780  
FIG. 781  
FIG. 782  
FIG. 783  
FIG. 784  
FIG. 785  
FIG. 786  
FIG. 787  
FIG. 788  
FIG. 789  
FIG. 790  
FIG. 791  
FIG. 792  
FIG. 793  
FIG. 794  
FIG. 795  
FIG. 796  
FIG. 797  
FIG. 798  
FIG. 799  
FIG. 800  
FIG. 801  
FIG. 802  
FIG. 803  
FIG. 804  
FIG. 805  
FIG. 806  
FIG. 807  
FIG. 808  
FIG. 809  
FIG. 810  
FIG. 811  
FIG. 812  
FIG. 813  
FIG. 814  
FIG. 815  
FIG. 816  
FIG. 817  
FIG. 818  
FIG. 819  
FIG. 820  
FIG. 821  
FIG. 822  
FIG. 823  
FIG. 824  
FIG. 825  
FIG. 826  
FIG. 827  
FIG. 828  
FIG. 829  
FIG. 830  
FIG. 831  
FIG. 832  
FIG. 833  
FIG. 834  
FIG. 835  
FIG. 836  
FIG. 837  
FIG. 838  
FIG. 839  
FIG. 840  
FIG. 841  
FIG. 842  
FIG. 843  
FIG. 844  
FIG. 845  
FIG. 846  
FIG. 847  
FIG. 848  
FIG. 849  
FIG. 850  
FIG. 851  
FIG. 852  
FIG. 853  
FIG. 854  
FIG. 855  
FIG. 856  
FIG. 857  
FIG. 858  
FIG. 859  
FIG. 860  
FIG. 861  
FIG. 862  
FIG. 863  
FIG. 864  
FIG. 865  
FIG. 866  
FIG. 867  
FIG. 868  
FIG. 869  
FIG. 870  
FIG. 871  
FIG. 872  
FIG. 873  
FIG. 874  
FIG. 875  
FIG. 876  
FIG. 877  
FIG. 878  
FIG. 879  
FIG. 880  
FIG. 881  
FIG. 882  
FIG. 883  
FIG. 884  
FIG. 885  
FIG. 886  
FIG. 887  
FIG. 888  
FIG. 889  
FIG. 890  
FIG. 891  
FIG. 892  
FIG. 893  
FIG. 894  
FIG. 895  
FIG. 896  
FIG. 897  
FIG. 898  
FIG. 899  
FIG. 900  
FIG. 901  
FIG. 902  
FIG. 903  
FIG. 904  
FIG. 905  
FIG. 906  
FIG. 907  
FIG. 908  
FIG. 909  
FIG. 910  
FIG. 911  
FIG. 912  
FIG. 913  
FIG. 914  
FIG. 915  
FIG. 916  
FIG. 917  
FIG. 918  
FIG. 919  
FIG. 920  
FIG. 921  
FIG. 922  
FIG. 923  
FIG. 924  
FIG. 925  
FIG. 926  
FIG. 927  
FIG. 928  
FIG. 929  
FIG. 930  
FIG. 931  
FIG. 932  
FIG. 933  
FIG. 934  
FIG. 935  
FIG. 936  
FIG. 937  
FIG. 938  
FIG. 939  
FIG. 940  
FIG. 941  
FIG. 942  
FIG. 943  
FIG. 944  
FIG. 945  
FIG. 946  
FIG. 947  
FIG. 948  
FIG. 949  
FIG. 950  
FIG. 951  
FIG. 952  
FIG. 953  
FIG. 954  
FIG. 955  
FIG. 956  
FIG. 957  
FIG. 958  
FIG. 959  
FIG. 960  
FIG. 961  
FIG. 962  
FIG. 963  
FIG. 964  
FIG. 965  
FIG. 966  
FIG. 967  
FIG. 968  
FIG. 969  
FIG. 970  
FIG. 971  
FIG. 972  
FIG. 973  
FIG. 974  
FIG. 975  
FIG. 976  
FIG. 977  
FIG. 978  
FIG. 979  
FIG. 980  
FIG. 981  
FIG. 982  
FIG. 983  
FIG. 984  
FIG. 985  
FIG. 986  
FIG. 987  
FIG. 988  
FIG. 989  
FIG. 990  
FIG. 991  
FIG. 992  
FIG. 993  
FIG. 994  
FIG. 995  
FIG. 996  
FIG. 997  
FIG. 998  
FIG. 999  
FIG. 1000